

MARELEC PR1 Printer

Robust construction
for humid
conditions

Flexible label design

High-speed printing

Suitable for
traceability



FEATURES

The best way to label your weighed products is the **MARELEC PR1** label printer. This stand-alone printer is fully compatible with our weighing and grading systems.

The **MARELEC PR1** printer has been designed especially for use in humid conditions. The printer is integrated in a protective case of stainless steel. Heating protects the printer against condensation.

CONSTRUCTION

Stainless steel protective case. AISI 316L

DIMENSIONS

350(l) x 300(w) x 250(h) mm

LABELS

1000 labels, 3x4"

HEATING

Integrated

FUNCTIONS*

- Printing : Direct thermal printing. Auto-calibration
- Print speed : 127 mm/s
- Resolution : 8 dots/mm
- Max. print area : Width: 104 mm, maximum length: 991 mm
- Max. roll size : Ø127 mm O.D. on a roll with Ø12.7 mm, 25.4 mm or 37.1 mm I.D.
(label and liner): 0.08 mm to 0.20 mm
- Ribbon width : 34 mm to 110 mm
- Sensors : Transmissive, reflective and paper detection sensors

* Subject to modifications

MARELEC

Food Technologies

Redanweg 15
8620 Nieuwpoort - Belgium
T +32 58 222 111
F +32 58 239 280
sales@marelec.com

www.marelec.com

